

SAN BRUNO FIRE DEPARTMENT INSPECTION RECORD

R-2

ADDRESS	BUS	INESS NAME		
MANAGER/OV	VNER	PHONE #		
Manual &	or Automatic Fire Alarm System	Fire Sprinklers	Hose Cabinets	
Monitorin	g Company: Name	Phone		
Knox Box	Location:	· · · · · · · · · · · · · · · · · · ·		
	A reasonable degree of fire safety exists at this time. Unit # E 51 E 52 T 51			
☐ In accorda violations	ance with Section 103.4.3.1 of the California immediately upon receipt of this notice.	a Fire Code you are hereby	ordered to correct all	
1 ST 2 ND NA OK	GENERAL REQUIREMENTS AND SPECIAL	HAZARDS FOR "R-2" OCC	<u>UPANCIES</u>	
O O O 1	A minimum of one 2-A:10-B:C fire extinguisher shall be provided for each 75 feet, CLEARLY visible, and mounted			
	42-48 " from the floor, a minimum of one per floor. 2 Fire extinguishers shall be serviced annually and shall have a current service tag attached.			
	Exits shall not be obstructed in any manner.	d by two lamps or shall be of the a	olf luminaua tuna	
□ □ □ □ 5	Exit signs shall be internally or externally illuminated by two lamps or shall be of the self-luminous type Fire rated door assemblies shall be maintained to automatically close and latch.			
	Extension cords shall not be used as a substitute for permanent wiring. Laundry, Electrical, Boiler & Water Heater rooms shall be maintained free of combustible storage.			
	Laundry Rooms & Dryers shall be maintained free of lint accumulation.			
□ □ □ □ 10	Maintain min. 18" clearance below fire sprinklers and 24" from ceilings without fire sprinklers. Where an automatic or manual fire alarm system is in place, such system shall be maintained in operating condition.			
O O O 11	Where an automatic extinguishing system or standpipe system is in place, such system shall be serviced and maintained in operating condition (inspected/serviced quarterly, re-certified every 5 years for fire sprinklers).			
	A clear depth of 36" and width of 30" shall be maintained from the face of electrical switchboards and panel boards.			
□ □ □ □ 13 □ □ □ □ 14	Storage, Boiler, Electrical and Laundry Rooms and carports shall maintain their current fire-resistive construction. Combustible storage or debris is not allowed under stairs or in carports.			
□ □ □ □ 15 □ □ □ □ 16	Operational smoke alarms are provided as required. Provide address numbers that are visible and legible from the street with minimum 6 " contrasting color, no metallic or shiny			
	finishes. Recommend illumination of address numbers.			
	Knox Box keys were check to verify being current.	that amaka alauma ay	o maintainad 0 taatad	
at least annua	ers shall maintain documentation lly.	that smoke alarms ar	e maintained & tested	
<u></u>	BLE TO ACCESS UNITS TO VERIFY OPERAT		FIRE EXTINGUISHERS	
If corrections	are not made by the date noted a	bove. citations may b	e issued. Minimum	
	for the first offense, \$200 for the	•		
	day of violation may constitute a			
A re- inspection to d have further question	letermine if you have complied with this order wins contact the Inspector at (650) 616-7096.	Il be conducted on or about	If you	
1 st Insp/	/ Owner/Mgr	Inspector (print)	A B C	
2''u Insp. /	/ Owner/Mgr Owner/Mgr	Inspector (print)	A B C	
R2inspectionform.020				